

MINIMALIST DOOR FRAME FIRE RATING INFORMATION SHEET

Overview: The Minimalist Door Frame has achieved a *fire rating of 20-minutes* as tested and verified by Underwriters Laboratory. A 20-minute fire-rated door frame can be used in a One-Hour fire-rated wall assembly.

Frames INCLUDED in 20-minute fire rating:

- All throat sizes 4 7/8" wide or wider
- All *single door* openings up to 36" wide x 96" high
- All finishes

Frames NOT INCLUDED in 20-minute fire rating:

- All throat sizes narrower than 4 7/8" including 3 1/2", 3 3/4" and 4 5/8"
- All *double door* frames
- Door openings wider than 36" and higher than 96"

Doors: All 1 3/4" single wood and steel doors that are 20-minute fire-rated or greater and are up to 36" wide and 96" high are acceptable.

Hardware: Exposed hinges: Must carry at least a 20-minute fire-rating.
Factory installed concealed hinges: All factory installed SOSS hinges (#218FR) carry a 20-minute fire-rating.
Other concealed hinges: Must carry at least a 20-minute fire-rating.
Must verify that hinges are compatible with Minimalist Door Frame.

Strikes/locksets: All strikes and locksets must be rated for use in one-hour rated wall assemblies.